

## CLAIM AMENDMENTS

### IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

1-9. (Cancelled)

10. (Previously Presented) A method for controlling a fuel pressure in a fuel supply device of an internal combustion engine having a regulator valve, the method comprising the steps of:

determining a desired fuel pressure value;

determining an actual fuel pressure value;

calculating an actual gradient selected from the group consisting of: an actual fuel flow rate gradient and an actual fuel pressure gradient;

comparing the calculated actual gradient to a specified threshold gradient value; and

if the calculated actual gradient is above the specified threshold gradient value then determining an actuating signal as a function of the desired fuel pressure value and the calculated actual gradient; and

controlling said regulator valve with said actuating signal.

11. (Cancelled)

12. (Previously Presented) A method for controlling a fuel pressure in a fuel supply device of an internal combustion engine, wherein the supply device has a fuel pump that pumps a fuel into a fuel accumulator that supplies injection valves with the fuel and that is connected to a regulator valve that adjusts the fuel pressure as a function of an actuating signal comprising the steps of:

- determining a desired fuel pressure value;
- determining an actual fuel pressure value;
- calculating an actual gradient selected from the group consisting of: an actual fuel flow rate gradient and an actual fuel pressure gradient;
- comparing the calculated actual gradient to a specified threshold gradient value; and
- if the calculated actual gradient is above the specified threshold gradient value then determining an actuating signal as a function of the desired fuel pressure value and the calculated actual gradient; and
- controlling said regulator valve with said actuating signal.

13. (Previously Presented) The method according to Claim 12, wherein the regulator valve is an electromagnetic regulator and an energization of the electromagnetic regulator is influenced by the actuating signal.

14. **(Currently Amended)** The method according to Claim 13, wherein the step of controlling said regulator valve with said actuating signal includes:

- if the flow rate increases, decreasing an energization of the electromagnetic regulator;
- and
- if the flow rate falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

15. **(Currently Amended)** The method according to Claim 13, wherein the step of controlling said regulator valve with said actuating signal includes:

if the fuel pressure increases, decreasing the energization of the electromagnetic regulator; and

if the fuel pressure falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

16. **(Currently Amended)** The method according to Claim 14, wherein the step of controlling said regulator valve with said actuating signal includes:

if the fuel pressure increases, decreasing the energization of the electromagnetic regulator; and

if the fuel pressure falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

17. **(Previously Presented)** The method according to Claim 12, further comprising if the calculated actual gradient is below said specified threshold gradient value then determining the actuating signal as a function of the desired fuel pressure value.

18. Cancelled

19. **(Previously Presented)** The method according to Claim 10, wherein the regulator valve is an electromagnetic regulator and an energization of the electromagnetic regulator is influenced by the actuating signal.

20. **(Currently Amended)** The method according to Claim 10, wherein the step of controlling said regulator valve with said actuating signal includes:

if the flow rate increases, decreasing an energization of the electromagnetic regulator;  
and

if the flow rate falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

21. **(Currently Amended)** The method according to Claim 19, wherein the step of controlling said regulator valve with said actuating signal includes:

if the fuel pressure increases, decreasing the energization of the electromagnetic regulator; and

if the fuel pressure falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

22. (Previously Presented) The method according to Claim 20, wherein the step of controlling said regulator valve with said actuating signal includes:

if the fuel pressure increases, decreasing the energization of the electromagnetic regulator; and

if the fuel pressure falls, ~~decreasing~~ increasing the energization of the electromagnetic regulator.

23. (Previously Presented) The method according to Claim 10, further comprising if the calculated actual gradient is below said specified threshold gradient value then determining the actuating signal as a function of the desired fuel pressure value.

24. Cancelled